



QUICK START GUIDE

AC1200 Wireless Outdoor Access Point



www.wavlink.com/en_us/Greenwood-5-1200G-B



Scan the QR code or load the link for
Quick Start Guide downloading




WAVLINK (@WavlinkOfficial)
WAVLINK SUPPORT (@WavlinkTechSupport)

Greenwood 5 1200G

Hardware Overview



Top view



Bottom view

- ① 2.4G RP-SMA Antenna Connectors
- ② 5G RP-SMA Antenna Connectors
- ③ 3 x Wi-Fi Signal LEDs
- ④ Status LED
- ⑤ WAN/LAN Backhaul LED

- ⑥ LAN LED
- ⑦ POWER LED
- ⑧ Reset/PAIR Button
- ⑨ LAN Port
- ⑩ WAN(PoE IN)/LAN Backhaul
- ⑪ Grounding Terminal

* This product supports 802.3 AT/AF Active PoE and Passive PoE to supply power.

Default Parameters

Web: <http://waplogin.link>

Default IP: 192.168.30.1

Login Password: [admin](#)




2.4G SSID: [WAVLINK-N_XXXX](#)




5G/AC SSID: [WAVLINK-AC_XXXX](#)

LED Indicators

Power	On	The device is powered on.
	Off	The device is not receiving electrical power.
LAN	On	The Ethernet port is connected.
	Off	The Ethernet port is disconnected.
WAN/LAN Backhaul	On	The Ethernet port is connected.
	Off	The Ethernet port is disconnected.
Status	Fast flash	Another router has not been connected when the device is in the repeater mode.
	Slow flash	The another router has been connected but the device has no access to the network in the repeater mode.
	On	The device keeps on in the AP mode; The device can access the network normally.



Wi-Fi Signal

Mode				Description
AP	ON	ON	ON	Wi-Fi signal output power 100%.
Repeater	ON	ON	ON	Better reception: signal 81%~100%.
	ON	ON	OFF	Good reception: signal 60%~80%.
	ON	OFF	OFF	Weak reception: signal below 0~59%.

Mode				Description
Mesh Router	ON	ON	ON	Wi-Fi signal output power 100%.
Mesh Extender	ON	ON	ON	Better reception: signal 81%~100%.
	ON	ON	OFF	Good reception: signal 60%~80%.
	ON	OFF	OFF	Weak reception: signal below 0~59%.

Installation

1. Please follow the installation steps when assembling the device.



- 1 Pass RJ45 cable through the spiral cover
- 2 Pass RJ45 cable through the rubber seal
- 3 Pass RJ45 cable through the holder
- 4 Connect the RJ45 cable to PoE IN/WAN port.
- 5 Spin 2.4G antenna into the 2.4G external RP-SMA connector
- 6 Spin 5G antenna into the 5G external RP-SMA connector
- 7 Screw the holder
- 8 Plug the rubber seal to the holder
- 9 Screw the spiral cover
- 10 Secure the antenna with a bracket.

2. Antenna bracket installation

- 1) Place the arrow pattern on the bracket snap toward the two antennas in the center.
- 2) Secure the antenna with a bracket.



3. Install the device.


- 3.1 Firstly fasten the device to somewhere firm, then install the device in the holder.



Remark

If you happen to live in the zone where lightning happens a lot, we suggest that you install the device through grounding connection in order to strengthen the lightning-resistant function.

- 3.2 Now please follow the steps below.



- 1) Connect the "**PoE**" port of PoE converter to the PoE IN(WAN) port of the device.
- 2) Connect "**LAN DATA IN**" to "**LAN**" of your router.
- 3) Plug in the device through the power adapter.
- 4) Push the "**ON/OFF**" button to turn on or off the device.

Attention


- 1) Ensure that you use a certified CAT5e/CAT6 Ethernet cable with RJ45 connectors.
- 2) Make sure the length of the Ethernet cable from PoE to the device is less than 100 meters (328ft).

Working Mode

This AP supports two work modes: FAT mode and FIT mode. Here is a brief introduction to the two work modes:


Case 1: FAT AP

- FAT mode means that the AP can be independently configured and has a separate management interface, just like a regular wireless AP.
- FAT mode is primarily used in small networks that do not use an AC Controller.




Here are several typical work modes for Fat AP:


AP/Router Mode



Repeater Mode



Router



Repeater




Case 2: FIT AP

FIT mode means that the AP is centrally controlled and managed by the WAVLINK AC (Wireless Access Point Controller).

If it works as a Fit AP, which is typically responsible only for data transmission and basic radio frequency management. All network decisions, configurations, security, and traffic control operations are handled by the WAVLINK AC.

Fit APs are typically used in an AC+AP network architecture and can only be utilized with the WAVLINK wireless access point controller, as shown in the diagram below.




FIT mode is ideal for larger networks with broader coverage, a higher number of users, and a need for efficient network performance and enhanced security.


Configuration(FAT AP Mode)

1. Connection


1.1 Via Wireless



Turn on your Wi-Fi, search SSID of this product on your wireless devices (smart phone, tablet computer, laptop, etc.) and connect to it.




For Windows users



For Mac users

1.2 Via Cable




Connect Ethernet cable to your PC/laptop and device's LAN port, then you can start configuring the device.

2. Normally, the product web UI will guide you to the login page once you have connected to the device successfully in your first time, but if it doesn't, please manually input <http://waplogin.link> in the address bar of your browser on PC/laptop or phone, the default password is [admin](#).



The image shows the WAVLINK login page. At the top is the WAVLINK logo with the tagline "see the world". Below that is the text "Welcome to WAVLINK". A red message says "Please set up this device first!". There is a text input field with the placeholder "Please enter your password" and a blue "Login" button below it.

3. Select your **Country/Region** and **Time Zone**. For your network security, we suggest that you set a new login password.




The image shows the WAVLINK configuration page. At the top, there are two tabs: "System" (selected) and "Network". Below the tabs, there are four sections: "Country/Region" with a dropdown menu, "Time Zone" with a dropdown menu, "Admin Password" with a text input field and a strength indicator (three colored bars), and "Confirm Password" with a text input field and a strength indicator. A "Next" button is at the bottom.

Note: The three colored bars in "**Admin Password**" area indicates the strength of the login password.


4. Mode Selection

This product has 4 modes. Click "**Switch Mode**" to switch mode.




4.1 AP Mode


1. The system selects AP mode by default, there is no need to select the AP mode manually. Click on "**Next**".
2. Connect the WAN/LAN port of this product to the poe and connect the lan data in port of the poe box to the host router via Ethernet cable. Then you can change the SSID or use the default one, the encryption mode recommend is **WPA2-PSK**. For your network security. please create a new password according to the rule. Then click on "**Save**" and wait for the setting process to complete.



4.2 Repeater Mode

1. Click "**Switch Mode**" and select Repeater Mode.
2. After scanning, please make sure the Wi-Fi you want to select is listed, and click "**Next**", if it isn't, please click "**Rescan**".









System


Network

☒ Select Wi-Fi
 ☐ Manual Input

Please select the wireless signal to be relayed

5G/2.4G


	WAVLINK_Guest_5G	<input type="radio"/>
	WAVLINK-AC_5854	<input type="radio"/>
	WAVLINK-Mesh_2366	<input type="radio"/>
	WAVLINK_Guest	<input type="radio"/>
	Wireless-AC_8294	<input type="radio"/>
	WAVLINK-AC_6532	<input type="radio"/>
	8888888888888888	<input type="radio"/>


Back

Rescan

Next

3. Enter the password for the wireless network of your selected. Set the wireless network encryption mode and password for this device. Click **"Save"**.


System


Network

Superior wireless network information

Superior Network Name

WAVLINK-AC_5854

Password

Try!

Wireless network information of this device

Connection Type

WISP-Recommend ▾

2.4G Wi-Fi Name

WAVLINK-AC_5854_EXT2.4G

2.4G Encryption

WPA2-PSK(Recommend) ▾

2.4G Wi-Fi password

Between 8—63 characters

Try!

5G Wi-Fi Name

WAVLINK-AC_5854_EXT5G

5G Encryption

WPA2-PSK(Recommend) ▾

5G Wi-Fi password

Between 8—63 characters

Try!

Back

Save

Manual Input:

1. Manually add the wireless network you want to relay, enter the device information, and click "**Next**".

The screenshot shows a web interface with two tabs: 'System' and 'Network'. The 'Network' tab is active. Below the tabs, there are two radio buttons: 'Select Wi-Fi' (unselected) and 'Manual Input' (selected). Below the radio buttons, the text 'Please input the wireless signal to be relayed' is displayed. There are four input fields: 'Superior Network Name' (text input), 'Frequency band' (dropdown menu with '2.4G' selected), 'Channel' (dropdown menu with 'Automatic(Recommend)' selected), and 'Encryption Mode' (dropdown menu with 'OPEN' selected). At the bottom, there are two blue buttons: 'Back' and 'Next'.


2. Set the wireless network encryption mode and password for this device. Click "**Save**".

The screenshot shows the same web interface as the previous one, but with the 'Manual Input' radio button selected. Below the radio buttons, the text 'Wireless network information of this device' is displayed. There are six input fields: 'Connection Type' (dropdown menu with 'WISP-Recommend' selected), '2.4G Wi-Fi Name' (text input with 'WAVLINK-AC_5854_EXT2.4G'), '2.4G Encryption' (dropdown menu with 'WPA2-PSK(Recommend)' selected), '2.4G Wi-Fi password' (text input with 'Between 8-63 characters' and a strength indicator), '5G Wi-Fi Name' (text input with 'WAVLINK-AC_5854_EXT5G'), '5G Encryption' (dropdown menu with 'WPA2-PSK(Recommend)' selected), and '5G Wi-Fi password' (text input with 'Between 8-63 characters' and a strength indicator). At the bottom, there are two blue buttons: 'Back' and 'Save'.

4.3 Mesh Router Mode

1. Click on "**Switch Mode**", then choose "**Mesh Router Mode**".
2. Before configuring, please make sure your upper router has connected to the WAN/LAN port of this product. The system will guide you to select the **WAN Type**. As for the Encryption Mode, we recommend you to select WPA2-PSK. For you network security, we suggest you create a Password.

You can add more devices that support WAVLINK Everything Mesh for networking in Mesh Router mode, refer to [5](#) for adding method.



The screenshot shows a web interface for configuring a network. At the top, there are two tabs: "System" (selected) and "Network". Below the tabs, there are four configuration fields:

- Wan Type:** A dropdown menu with "DHCP" selected.
- SSID:** A text input field containing "WAVLINK-N_8312".
- Encryption Method:** A dropdown menu with "WPA2-PSK(Recommend)" selected.
- Password:** A text input field with a placeholder "Between 8~63 characters" and a strength indicator (three bars) and a lock icon.

At the bottom, there are two buttons: "Back" and "Save".

Which WAN Type am I supposed to choose?

If you use DSL line and you are only provided an account name and a password by your ISP, choose PPPoE. If you use cable TV or fiber cable, choose DHCP(Dynamic IP). If you are provided information such as IP address, Subnet Mask and Default Gateway, choose Static IP.

4.4 Mesh Extender Mode

If you have a router that supports WAVLINK Everything Mesh function, then you can build a mesh system with this mode.

1. Click on "**Switch Mode**". Then choose "**Mesh Extender Mode**".

System | Network

Country/Region: [Switch mode](#)

Time Zone:

Admin Password: [?/x](#)

Confirm Password: [?/x](#)

[Next](#)

2. Select your Country/Region and Time Zone. Enter the Admin Password. After click "**Start Pairing**", follow 5 to add this device on the primary router.

System | Network

Country/Region:

Time Zone:

Admin Password: [?/x](#)

Confirm Password: [?/x](#)


[Start Pairing](#)

When the device enters the pairing state, please Keep pressing the PAIR button 2s of the primary router or add the mesh device in the primary router configuration page, the pairing time is expected to be 2 minutes. If the pairing fails, check whether the primary router is set correctly, and then enable re-pairing via the pairing button or re-enter this device page. If you want to switch to another mode when you have successfully configured Mesh Extender Mode, please reset this device.


5. If you need to add more mesh devices to build up a stronger network in your home.you simply need to pair the new mesh devices with the existing network.

Pairing on the web

1. Log in to <http://waplogin.link>.
2. **“Advanced”** -> **“Mesh Network”**.
3. Click on **“Add”** and then follow the prompts on the screen.




4. After scanning, please make sure the device you want to add is listed, and click **“Add”**. If not, make sure the Mesh extender to be added is in a paired state. Click **“Rescan”**.



Pairing with Pair Button

After configuring the main router and when the main router has the network, press and hold the pair button for both the main router and the mesh extender for 2 seconds. When LED lights become solid blue, the pairing process is successfully completed.



Wi-Fi Password Management

When you need to change your Wi-Fi password, please click on **“Wireless”**.

The screenshot shows the Wavlink web interface. The top navigation bar includes 'Home', 'Terminal', 'Wireless', 'Advanced', and 'Device'. The 'Wireless' tab is selected. Below the navigation bar, there is a toggle switch for 'Enable it to make 2.4G and 5G Wi-Fi dual bands in one SSID'. The main settings area is titled 'Wi-Fi' and contains the following fields:

- SSID:** WAVLINK-N_8312
- Encryption Method:** WPA2-PSK(Recommend)
- Password:** A field with masked characters (dots) and a strength indicator bar below it.


Below the main settings area, there is an 'Advanced >' link and a 'Save' button at the bottom.


Firmware Upgrade

If you need to update firmware, please proceed as the following steps:

Option I


Local Upgrade

1. Download the latest firmware file.
2. Extract the firmware from the downloaded file.
3. Log in to <http://waplogin.link> then choose “Advanced” and select “Firmware Update”.
4. Click on  to locate the extracted firmware file.
5. Click on “Upload” and choose “Apply”, and wait for the firmware upgrade process to complete.



The screenshot shows the Wavlink web interface with the 'Firmware Update' section selected. Under 'Local Upgrade', there is a table for selecting devices to upgrade. The table has two columns: 'Mesh Node Name' and 'Current SW Version'. A checkbox is next to each row. Below the table is a 'Choose File' button and an 'Upload' button. A note at the bottom states: 'Manually download files on WAVLINK official website, and upload and upgrade locally. The following devices are of the different model and need to be upgraded after clicking on the link.'

	Mesh Node Name	Current SW Version
<input type="checkbox"/>	Router	MT2HP3_V000000X


Upgrade File 

	Mesh Node Name	Current SW Version	Upgrade Link
--	----------------	--------------------	--------------

Option II

Online Upgrade

1. Log in to <http://waplogin.link> then choose “Advanced” and select “Firmware Update”.
2. Select the Mesh Node Name that needs to be upgraded.



The screenshot shows the 'Online Upgrade' section of the Wavlink web interface. It includes a table with columns: 'Mesh Node Name', 'MAC Address', 'Current SW Version', 'Latest Software Version', and 'Status'. There are checkboxes for each row. Below the table are two buttons: 'Check New Version' and 'One-Click Upgrade'. A note at the top states: 'In the case of connecting to the network, then check the device that needs to be upgraded, after checking the latest software version, click one-click upgrade to upgrade.'

	Mesh Node Name	MAC Address	Current SW Version	Latest Software Version	Status
<input type="checkbox"/>	Router	81:00:00:00:04:8F	MT2HP3_V000000X	No New Version	Non-Upgradeable

Note: After updating firmware, please Reset The Device And Clear Your Browser Cache.

What is firmware upgrade and why do I need it?

Firmware contains fixed for bugs and new features, please keep the latest firmware to improve the experience of using the product. Please do not use the wrong firmware, otherwise, it will damage your device and void the product warranty.

For more details, please visit our website www.wavlink.com

Our Technical Support: support@wavlink.com

FAQ

Q1. What can I do if I can not access the Internet?

- Make sure your Internet works normally, please contact your ISP(Internet Service Provider) if it doesn't.
- Initiate your browser, enter <http://waplogin.link>, then set up the following quick start guide.
- Reboot your device and try it again.

Q2. Why can't I visit the web UI by inputting

<http://waplogin.link>?

- If you can't log in to URL in AP Mode, please check the IP address arranged by the upstream router, then try to restart the process.
- Make sure you have connected to the WiFi of the Wavlink device.
- Please try to clean the cache of the browser.
- Try to log in the management page via another browser.
- Try to log in the management page via other devices.

Q3. What can I do if I forget my administration management password?

- Please reset the device, the default password is [admin](#).

Q4. How do I find the best location for mesh devices?

- Please put your mesh devices in a relatively open space to avoid obstacles such as metal objects, reinforced concrete walls and so on.

Please visit https://www.wavlink.com/en_us/fag.html for more details.

GNU GENERAL PUBLIC LICENSE NOTICE

This product includes software codes developed by third parties. These software codes are subject to either the GNU General Public License (GPL), Version 2, June 1991 or the GNU Lesser General Public License (LGPL), Version 2.1, February 1999. You can copy, distribute, and/or modify in accordance with the terms and conditions of GPL or LGPL.

The source code should be complete, if you want us to provide any additional source code files under GNU General Public License (GPL) please contact us in these matters. We are committed to meeting the requirements of the GNU General Public License (GPL). You are welcome to contact our local office to get the corresponding software and licenses. Please inform us of your contact details (full address) and the product code. We will send you a software package with the software and license for free.

The respective programs are distributed WITHOUT ANY WARRANTY; without even the implied warranty Of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

Please refer to the GNU General Public License website for further information.

<http://www.gnu.org/licenses/old-licenses/lgpl-2.0.html>

<http://www.gnu.org/licenses/gpl.html>

WEEE Directive & Product Disposal



At the end of its serviceable life, this product should not be treated as household or general waste. It should be handed over to the applicable collection point for the recycling of electrical and electronic equipment, or returned to the supplier for disposal.

Need help?

We're here for you!



Online support: [wavlink.com](https://www.wavlink.com)

Available Mon-Fri 8:30 am-5:30pm (UTC+8)



support@wavlink.com

Available Mon-Fri 8:30 am-5:30pm (UTC+8)



+1 8889730883 (US Local)

Mon-Fri 9:00 am - 10:00 pm (UTC-5)

www.wavlink.com



**Thank you for purchasing
WAVLINK product!**